

CONSTRUCTIONAL THICKNESS VENEER

ASH - 1.4mm and 2.4mm

BAMBOO - 3mm

BEECH (STEAMED) - 1.4mm, 2.00mm, 2.4mm, 5.00mm

BEECH (WHITE) - 1.4mm

CEDAR OF LEBANON - 1.5mm, 2.00mm

CEDAR, WESTERN RED - 1.5mm

CHEN CHEN - 1.5mm

CHERRY, AMERICAN - 1.5mm and 2.5mm

CHERRY, EURO - 1.00mm

DOUGLAS FIR (EUROPEAN) - 1.4mm

EBONY, MACASSAR - 1.5mm

ELM, AMERICAN RED - 1.5mm

ELM, EUROPEAN - 1.4mm and 2.4mm

HORNBEAM - 1.00mm

IROKO - 2.0mm, 2.4mm

KHAYA - 1.5mm, 2.00mm, 2.5mm, 4.0mm

LARCH - 1.4mm, 2.4mm

MAHOGANY, STH. AMERICAN - 1.4mm, 2.5mm

MAPLE, HARD - 1.5mm, 2.5mm

MERANTI - 1.8mm

OAK, AMERICAN WHITE - 1.5mm, 2.5mm

OAK, EUROPEAN - 1.00mm, 1.4mm, 2.4mm, 4.00mm, 4.5mm

OAK, BROWN - 1.4mm, 2.4mm

OAK, FUMED - 1.4mm, 2.4mm, 4.5mm

OAK, PIPPY - 1.5mm, 2.5mm

OLIVE ASH - 1.5mm

PEARTREE - 1.4mm, 2.4mm

PINE, EUROPEAN - 1.4mm

PINE, OREGON - 1.4mm

ROSEWOOD, INDIAN - 1.5mm

ROSEWOOD, MEXICAN - 1.4mm

SAPELE - 1.5mm and 2.5mm

SIPO - 2.4mm

SYCAMORE - 1.4mm, 2.8mm

TEAK - 1.5mm, 2.5mm

WALNUT, AMERICAN - 1.5mm, 2.5mm

WALNUT, EUROPEAN - 2.0mm

WENGE - 1.5mm and 2.5mm

ZEBRANO - 1.5mm